



MarClean AC

- Alkaline NLS Cargo Tank Cleaner

Description:

MarClean AC is an alkaline NLS cargo tank cleaner with fast-acting wetting agents. It can be used neat or diluted with water depending on the contamination, type of surface, hardness of water and temperature.

- Removes animal fats and veg oil residues (drying / semi-drying).
- Leaves no film in the cargo tanks.
- Non-flammable.
- Fully biodegradable.
- Effective and economical in use.
- Approved by IMO.
- Approved by major coating manufacturers.

Direction for Product Use:

1. Pre-clean the tank with warm or hot SW, depending on oil type.
2. Make preferable FW solution of 1-5% MarClean AC in the service tank.
3. Re-circulate the solution at 65°C-70°C for 1-4 hours, one solution is usually sufficient to clean 3-4 tanks.
4. Rinse the tanks for 1-3 hours with warm SW, approximately 55°C-60°C.



High Quality Cleaning
Chemicals since 1994

Quality Without
Compromise

Approved By



MARPOL
International Convention for the Prevention of Pollution from Ships

Coating
Manufacturers

TECO Chemicals AS
Lilleakerveien 6D
0283 Oslo
Norway

WEB:

WWW.TECOCHEMICALS.COM

Email:

CHEMICALS@TECO.NO

Phone:

+47 67 200 300

Read the Material Safety
Data Sheet and Safety
Handling Sheet before using
this product.

Use protective equipment
and comply with disposal
considerations.

Updated MSDS and Safety
Handling Sheets are
available on
WWW.TECOCHEMICALS.COM

Directions when Mixing with Seawater

1. Seawater may reduce the foaming qualities of the detergent.
2. Seawater may influence the pH of the cleaning solution with a reduced cleaning effect as result.
3. Seawater represents a corrosion risk to the surfaces and the equipment used.
4. When mixing MarClean AC with seawater it is recommend to have a concentration of at least 1 - 5%.

IMO Approved & Tank Coating Manufacturer Approved

MarClean AC is approved by MARPOL / IMO in accordance with MEPC.1/Circ. 590. MarClean AC can safely be disposed into seawater without being harmful to the marine environment. MarClean AC is in compliance with MARPOL Annex V, and is also approved by major coating manufacturers.

Caution!

This product should not be used on zinc coating.

Properties

Physical state	: Liquid
Odour	: Characteristic
Colour	: Clear
Solubility in water	: Soluble in Water
Density	: 1.05 – 1.10 g/cm ³
pH	: 13.0 – 14.0

Packing

MarClean AC is accessible in 25ltr pails and 200ltr drums.

Stock Availability



TECO Chemicals – Available in



CODE: 3713



CODE: TN-262299



CODE: VIF-B89



CLEANQUOTE



MARINE
ONLINE

TECO

High Quality Cleaning
Chemicals since 1994

Quality Without
Compromise

Approved By



MARPOL

Coating
Manufacturers

TECO Chemicals AS

Lilleakerveien 6D

0283 Oslo

Norway

WEB:

WWW.TECOCHEMICALS.COM

Email:

CHEMICALS@TECO.NO

Phone:

+47 67 200 300

Read the Material Safety
Data Sheet and Safety
Handling Sheet before using
this product.

Use protective equipment
and comply with disposal
considerations.

Updated MSDS and Safety
Handling Sheets are
available on
WWW.TECOCHEMICALS.COM