



MarClean H60+

- Heavy Duty Solvent Based NLS Cargo Tank Cleaner

Description

MarClean H60+ is a low-toxic, low aromatic, biodegradable, solvent-based tank cleaner containing emulsifying agents and petroleum solvents. MarClean H60+ is safe to use on most metal surfaces and tank coating. MarClean H60+ is an excellent option for cleaning of paraffins, waxes and other mineral oils. The product does not leave any film in the cargo tanks, and it contains no chlorinated hydrocarbons. MarClean H60+ is a good solution, because its:

- Flashpoint above 60 °C.
- Effective and economical in use.
- Do not hinder re-refining of oil slops.
- Approved by IMO.
- Approved by major coating manufacturers.

Directions for Use

Re-circulation Method:

Mix a solution of 1–7% MarClean H60+ in freshwater or seawater in a mixing tank. Then re-circulate the blended solution into the tanks to be cleaned. Let the solution sit in the tank with re-circulation for up to 4-8 hours at 65°C. When you have made one solution, the solution is normally sufficient to clean almost 3–4 tanks. After the recommended re-circulation time, rinse the tank with lots of seawater or freshwater. The result is a clean tank, ready to carry the next cargo!

Spray Method:

Spray MarClean H60+ un-diluted on to the soiled surface. Let the product work at least for 30 minutes, but no more than 2 hours. Do not let the product to dry on wall. This can cause problems. So be aware of this when using this method with MarClean H60+. After the required worktime of the product, please rinse the applicated surfaces with warm seawater. Let then the surface dry, and the result is a clean surface.

TECO

High Quality Cleaning
Chemicals since 1994

Quality Without
Compromise

Approved By



MARPOL

Coating
Manufacturers

TECO Chemicals AS
Lilleakerveien 6D
0283 Oslo
Norway

WEB:

WWW.TECO-CHEMICALS.COM

Email:

CHEMICALS@TECO.NO

Phone:

+47 67 200 300

Read the Material Safety
Data Sheet and Safety
Handling Sheet before using
this product.

Use protective equipment
and comply with disposal
considerations.

Updated MSDS and Safety
Handling Sheets are
available on
WWW.TECO-CHEMICALS.COM

IMO Approved & Tank Coating Manufacturer Approved

MarClean H60+ is approved by MARPOL / IMO in accordance with MEPC.1/Circ. 590. MarClean H60+ can safely be disposed into seawater without being harmful to the marine environment. MarClean H60+ is in compliance with MARPOL Annex V, and is also approved by major coating manufacturers.

Caution!

Please do necessary arrangements for protection gear and equipment prior using this product.

Properties

Physical state	: Liquid
Odour	: Characteristic
Colour	: Colourless
Solubility in water	: Emulsable in Water
Density	: 0.80 g/cm ³
pH	: N/A

Packing

MarClean H60+ is accessible in 25ltr pails and 200ltr drums.

Stock Availability



TECO Chemicals – Available in



High Quality Cleaning
Chemicals since 1994

Quality Without
Compromise

Approved By



MARPOL

Coating
Manufacturers

TECO Chemicals AS
Lilleakerveien 6D
0283 Oslo
Norway

WEB:

WWW.TECO-CHEMICALS.COM

Email:

CHEMICALS@TECO.NO

Phone:

+47 67 200 300

Read the Material Safety
Data Sheet and Safety
Handling Sheet before using
this product.

Use protective equipment
and comply with disposal
considerations.

Updated MSDS and Safety
Handling Sheets are
available on
WWW.TECO-CHEMICALS.COM